



FLAMMABLE LIQUID RECOVERY

FLAMMABLE LIQUID RECOVERY VACUUM

Pneumatic Operated Vacuum

General Overview

- Meets GSA (General Services Administration) specification for air operated pneumatic vacuum cleaner for the recovery of flammable liquids.
- Specifically designed for the safe recovery of jet fuel and hazardous/flammable liquids
- Air operated vacuum creates high air flow and high static lift for recovering large amounts of liquid debris quickly and safely
- Ideal for applications where electricity is not available

Key Features

- Unit is air-operated with no moving parts, thus simplifying maintenance
- A silencer attached to the unit makes this vacuum quieter than any comparable vacuum at 80 dba
- Includes automatic shut-off when full for wet applications
- Sturdy all-steel dolly with 5" conductive wheels for easy transporting
- Explosion-proof tool kit with 14" floor squeegee tool standard.
- Special neoprene 25' x 1-1/2" grounded vacuum hose with Nitrile Core
- Pressure relief valve
- Intake hose closure
- Locking lid latches

Walk-Behind Scarifiers



Hand-Held Scarifiers



Needleguns



Impact Tools



Sanders and Abrasives



Specialty Products



Critical Filter Vacuums



Hoses & Fittings



*** Picks up 45 Gallons in under 60 seconds***

Specifications	340.87355.01
Wet Capacity	45 gallons (170 liters)
Dry Capacity	7.16 cu.ft. (.2 meters)
Static Lift	180+ inches (4572 mm)
Air Flow	182+ cfm (5.1 m)
Air Line Size	1/2 inch (12.7 mm)
Input Press	100 P.S.I. (7 Bar)
Input Air (CFM)	46 (1.3m/min)
Wheel Size	(4) 5 inch (12.7cm)
Weight	181 lbs. (82 kg)



Desco Mfg. Co., Inc.

23031 Arroyo Vista • Rancho Santa Margarita, CA 92688
www.descomfg.com • info@descomfg.com • (800) 337-2648