



DESCO SP-90

DESCO SP-90 SURFACE PREP MACHINE

The Desco SP-90 machine is ergonomically designed to accommodate operator "walk behind" operation. The "T-handle" consists of a finger deadman switch for power shut off. The unit comes with an 8 foot cord with a 3 prong, grounded male plug. The hub incorporates a single laminated abrasive hub made from Radial Bristle Discs, designed for surface preparation of horizontal and 90 degree applications. The guard can be adjusted 360 degrees. The Desco SP90 motor has a swivel coupling that can adjust from a 0 to 90 degree angle. The machine is designed with a front height adjustment wheel, to allow for proper hold-down pressure of the abrasive and prevent premature wear on the bristle hub. All steel and aluminum components are powder coated, plated or anodized to minimize corrosion from industrial & marine environments.

SPECIFICATIONS:

- Motor: 2.2 HP, 15 amp, 110v
- Amperage: 15
- RPM: 6000
- Volts: 110
- Spindle Thread: 5/8 x 11
- Cord: 8ft, 14-3 gage,
- 3 prong, grounded plug
- Weight: 32 lbs
- Hub: Quick Change
- Abrasive: 7 inch 50 Grit
- Radial Bristle



Desco Mfg. Co., Inc.

23031 Arroyo Vista • Rancho Santa Margarita, CA 92688
www.descomfg.com • info@descomfg.com • (800) 337-2648